


H42-042-30-075-V2

Outdoor IP67 / IK10
Adjustable 24V / 56VDC PoE Switch




Features

- Adjustable 24W@24VDC or 56VDC PoE port x1
- Flexible SFP transceiver port for uplink
- IP67 standard
- IK10 impact rated cast aluminum housing
- Operating temperature between -40°C and 65°C
- 30W@56VDC IEEE802.3at PoE port x4
- Supporting 10/100/1000Mbps data rates
- 6KV PoE surge protection
- IEEE 802.3az Energy Efficient Ethernet standard for green power

Applications










Security Center



Specifications

H42-042-30-075-V2	
Networking Specifications	
Total Gigabit Ports	6
Gigabit 802.3 at PoE Port (10M/100M/1G)	30W@56VDC x4
Gigabit 24VDC or 56VDC PoE Port (10M/100M/1G)	Adjustable 24W@24VDC or 56VDC x1
Gigabit SFP Slot	1
Forwarding Capacity	11.904Mpps
Mac Table	8k
Jumbo Frames	9,216 Bytes
Switching Capacity	12 Gbps
Power Specifications	
Input Voltage	100VAC ~ 240VAC 280VAC 4hr 300VAC 1min.
Backup Power Input Voltage	56VDC
Output Voltage Range / port 1~port 4	56 VDC PoE IEEE 802.3af (Max. 15.4W) output PoE+ IEEE802.3at (Max. 30W) output
Output Voltage Range / port 5	Adjustable 24W@24VDC or 56VDC x1
Power Budget	75W
Surge Protection / each PoE Port	6KV
Surge Protection for AC power	10KV
Mechanical Specifications	
Dimensions (L x W x H)	255.2 x 199.9 x 130 mm
Weight	3.2 kg (7.05 lb)
Connectors	M25 x 2
Environmental Specifications	
Weather Rating	IP67
Vandal Proof	IK10
Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Operating Humidity	5% ~ 95% non-condensing
Certifications	
EMC	CE, FCC, VCCI, C-Tick Class A
Safety	EN60950-1, IEC60950-1
Surge	EN61000-4-5

Optional Accessories

SFP Modules			
 <p>SFP-ISX-X5 Industrial Gigabit SFP Transceiver</p> <ul style="list-style-type: none"> • MMF • 0.5 km • -40°C ~85°C 	 <p>SFP-ISX-02 Industrial Gigabit SFP Transceiver</p> <ul style="list-style-type: none"> • MMF • 2 km • -40°C ~85°C 	 <p>SFP-ILX-10 Industrial Gigabit SFP Transceiver</p> <ul style="list-style-type: none"> • SMF • 10 km • -40°C ~85°C 	 <p>SFP-ILX-40 Industrial Gigabit SFP Transceiver</p> <ul style="list-style-type: none"> • SMF • 40 km • -40°C ~85°C
Pole Mount Brackets		Corner Mount Bracket	
 <p>AT-100 Pole Mount Adapter</p>	 <p>AT-101 Pole Mount Adapter</p>	 <p>AT-200 Corner Mount Adapter</p>	