

## Description

The S2620R-P is a new generation Ethernet intelligent access switch. It is mainly deployed on the IP MAN and intranets, meeting requirements the requirements of carrying various Ethernet services and accessing the Ethernet. It also provide the PoE function for powering of wireless LAN (WLAN) access points, IP security cameras, VoIP telephone and other low port density installations.

The S2620R-P is a case-shaped device with a chassis of 1U high. It provides 16 10/100/1000Base-TX ports + 2 gigabit SFP+2giga RJ45 ports. It provides 8/16 PoE.

## Features

- IEEE802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3af IEEE802.3at
- Provides 16 10/100/1000 Base-TX ports + 2 gigabit SFP ports+2giga RJ45 ports
- Provides 8/16PoE
- Build-in power supplies, 270W
- High back-plane bandwidth 40Gbps



Networking Interfaces	16 x 10/100/1000 Mbps RJ45 Ethernet Ports 2 x 1 Gbps SFP Ethernet Ports ,2giga RJ45 ports
LED Indicators	Power, Link/Act, PoE
Switching Capacity	40 Gbps
Forwarding Capacity	38.7 Mpps
Forwarding Mode	Store and Forward
Packet Buffer Memory	4.1 Mbit
MAC Address Table	8K
PoE Budget	250W
Dimensions	440 x 200 x 44 mm
Operating Temperature	0 to 40°C
Storage Temperature	-10 to 70°C
Operating Humidity	5 to 95% Noncondensing
Power Method	100-240VAC, 50/60Hz
Max. Power Consumption	Including PoE Output: 270W / Excluding PoE Output: 20W
EMC Safety	FCC, CE, RoHS
PoE Interfaces	Ports 1-16
PoE Standard	IEEE802.3af, IEEE802.3at
Max. PoE Wattage per Port	30W
PoE Voltage	52VDC
PoE Pin Assignment	V- (RJ45 Pin1,2), V+ (RJ45 Pin 3,6)