



Chipset	Atheros AR9344			
Memoria	DDR2 128MB			
Almacenamiento	8MB Flash			
IC	SiGe2576L*2			
Puerto	10/100/1000Mbps LAN*1			
Velocidad	300Mbps			
Transmisión	DSSS			
Modulación	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK			
Estándar	IEEE802.11n, IEEE802.11g, IEEE802.11b, IEEE802.3u,			
Protocolo	CSMA/CA, TCP/IP, IPX/SPX, NetBEUI, DHCP, NDIS3, NDIS4, NDIS5			
Canal	2312 - 2732MHz			
Disipación de alimentación	≤6W			
Alimentación	POE 24V 1A			
RF @25°C ±2dB	802.11b	27±2dBm		
	802.11g	6-24Mbps	26±2dBm	
		36-48Mbps	25±2dBm	
		54Mbps	24±2dBm	
802.11n	HT20 / HT40	MCS 7	22±2dBm	
Sensibilidad	802.11b	6Mbps ≤ -82; 54Mbps ≤ -65		
	802.11g	MCS 0 ≤ -86; MCS 7 ≤ -68		
	802.11n	HT20	MCS 7 ≤ -65dBm	
		HT40	MCS 7 ≤ -62dBm	
Antena	Externa, tipo N			
Gestión	Gestión WEB	SNMP MIB	Telnet	Serial
Security	Encriptación	WEP 64/128bits, WPA, WPA2, 802.1x		
Ambiente	Temp. uso -30° a +65°C	Temp. alm. -50° a +80°C	Humedad 95% sin condensación	
Físicas	224.5 x 274.5 x 58 mm	1.75 Kg		