

VideoXpert Shared Display

Product Features

- Operators can send video to surveillance personnel who need it most

With the support of VxOpsCenter utilizing Shared Display mode, the Shared Display Decoder provides monitor-wall functionality. Users can send tabs and video to the Shared Display and control the Shared Display remotely.



Technical Specifications

Hardware

| Item | Specification |
|------------------|---------------------------|
| Processor | Intel® Core™ i7-9700T |
| Memory | 8 GB DDR4 |
| Operating System | Windows 10 IoT Enterprise |
| SSD Storage | 128 GB |
| USB Ports | |
| USB 3.1 | 1x front, 4x rear |
| USB 3.1 Type-C | 1x front |

Video

| Item | Specification |
|-----------------|----------------------|
| Video system | Intel UHD Graphics |
| Memory | Shared |
| Video Outputs | 2x DisplayPort, HDMI |
| Max Resolution | |
| DisplayPort | 1920 x 1080 at 60 Hz |
| HDMI | 1920 x 1080 at 60 Hz |
| Video Standards | |
| NTSC | 60 Hz |
| PAL | 50 Hz |

Networking

| Item | Specification |
|------------|---|
| Interface | Gigabit Ethernet (1000Base-T) port (1x) |
| IP version | IPv4 |

Front Panel

| Item | Specification |
|------------------|-----------------------|
| Button | Power |
| Indicators | |
| Unit Status | White, flashing white |
| Primary Network | Green, orange, off |
| Hard Disk Status | Flashing white |

Power

| Item | Specification |
|-------------------|--------------------------------------|
| Power Input | 100 to 240 VAC 50/60 Hz, autoranging |
| Power Supply | External, 90 W |
| Power Consumption | 19.5 VDC, 4.62 A |

Environmental

| Item | Specification |
|---------------------------------|-----------------------------------|
| Operating Temperature | 5° to 35°C (41° to 95°F) |
| Non-Operating Temperature | −40° to 65°C (−40° to 149°F) |
| Operating Relative Humidity | 20% to 80%, non-condensing |
| Non-Operating Relative Humidity | 10% per hour |
| Operating Altitude | −15 to 3,048 m (−50 to 10,000 ft) |
| Operating Vibration | 0.66 GRMS |



Note: The temperature at the unit air intake can be significantly higher than room temperature. Temperature is affected by rack configuration, floor layout, air conditioning strategy, and other issues. To prevent performance failure and unit damage, make sure the temperature at the unit is continuously within the operating temperature range.

Physical

| Item | Specification |
|------------------------|---|
| Construction | Steel and plastic cabinet |
| Finish | Black |
| Dimensions (D x W x H) | 3.6 x 17.8 x 18.2 cm (1.4 x 7.0 x 7.2 in) |
| Mounting (RU) | VESA mount included |
| Unit Weight | 1.18 kg (2.60 lb) |

Certifications

| Item | Specification |
|---------------|---------------|
| CE | Class B |
| FCC, Part 15 | Class B |
| ICES-003 | Class B |
| UL/cUL Listed | Yes |
| C-Tick | Yes |
| CCC | Yes |
| KC | Yes |

Model Number

- **VX-A4-SDD** VideoXpert Shared Display with VESA mount; and US, Europe, and United Kingdom power cords



Pelco, Inc.
625 W. Alluvial, Fresno, California 93711 United States
(800) 289-9100 Tel
(800) 289-9150 Fax
+1 (559) 292-1981 International Tel
+1 (559) 348-1120 International Fax
www.pelco.com

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
⚠ ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.
⚠ AVERTISSEMENT: Cancer et Troubles de l'appareil reproducteur - www.P65Warnings.ca.gov.

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. ONVIF and the ONVIF logo are trademarks of ONVIF Inc. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice.

© Copyright 2019, Pelco, Inc. All rights reserved.