

- Sony 2MP 1/2.8" CMOS sensor
- HD 1080P Resolution, Image clear, Delicate
- HD lens: 3.6mm
- Day/Night(Auto ICR)
- Auto electronic shutter time
- IR range: 15 LED lamps 10m
- Ingress Protection: IP66
- Support DWDR, 3D DNR
- H.265 high profile
- Mobile phone remote monitoring (iOS, Android)
- Multi browser access (IE, Chrome, Firefox, Safari)
- Information superposition ( ID, IP, DDNS etc.)
- Support WEB, CMS, VMS, MYEYE, Cloud services
- Support HVR/NVR, Onvif protocol
- Support Mirco SD card
- WiFi



<b>Camera</b>	<b>Sensor</b>	2MP 1/2.8" CMOS sensor
	<b>Min. Illumination</b>	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	<b>Shutter time</b>	1/50(1/60)s to 1/10,000 s
	<b>Lens</b>	HD lens 3.6mm
	<b>Lens mount</b>	M12
	<b>Day&amp;night</b>	IR cut filter with auto switch
<b>Image</b>	<b>Max.image</b>	1920*1080
	<b>Frame rate</b>	PAL:1080P@12fps / NTSC: 1080P@12fps
<b>Compression</b>	<b>Video</b>	H.265 High Profile, JPEG snapshot
	<b>Bite rate</b>	0.1Mbps-6Mbps
	<b>Audio</b>	G.711a
<b>Network</b>	<b>Storage</b>	Network storage
	<b>Alarm</b>	Motion detection, video loss, video block, etc.
	<b>Protocol</b>	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HT-TPS, SIP, 802.1x, IPv6 option )
	<b>Features</b>	anti-flicker, dual-stream, heartbeat, password protection
<b>Interface</b>	<b>Ethernet</b>	1*10/100Mbps Ethernet port, RJ45 port
<b>General</b>	<b>Temperature / Humidity</b>	-10°C to +60°C / 10%-90% RH
	<b>Power supply / Consumption</b>	DC12V±10% / MAX 3W
	<b>IR range</b>	15 LEDS "IR2":10 meters
	<b>Ingress protection</b>	IP66
	<b>Weight / Dimension</b>	400g / 85mm*60mm